

## Epatec IPC 322



### Features:

- ◇ All aluminum structure, fanless design;
- ◇ Onboard 8<sup>th</sup> or 10<sup>th</sup> Intel Core i3 i5 i7 processor;
- ◇ TPM 2.0 security encryption for Windows 11;
- ◇ 1\*DDR4 slot, Max. 32GB;
- ◇ 1\*M.2 2280 slot, 1\*2.5" SATA;
- ◇ 2\*COM(COM1, COM2 RS232/RS485);
- ◇ DC 12V Input;
- ◇ Support OS:



Material	High-quality all aluminum, surface anodic oxidation
Processor	Onboard Intel Core i3 10110U (Dual core quad threads, 2.1GHz, Max turbo 4.1GHz) Onboard Intel Core i5 8260U (Quad core eight threads, 1.6GHz, Max turbo 3.9GHz) Onboard Intel Core i5 10210U (Quad core eight threads, 1.6GHz, Max turbo 4.2GHz) Onboard Intel Core i7 10810U (Six core twelve threads, 1.1 GHz, Max turbo 4.9GHz)
RAM	Support 1*DDR4 2400/2666 SODIMM Slot, Max. Support 32GB
BIOS	AMI EFI BIOS
Display Chip	Intel UHD Graphics 620 for i5-8260U; Intel UHD Graphics for 10th Gen Intel Processors
Front I/O	2*COM (COM1, COM2 RS232 or RS485), 4*USB3.1, Power Switch, SIM Slot
Rear I/O	1*DC, 2*USB2.0, 1*HDMI, 1*DP, 2*Intel LAN, 1*Audio (Mic&Speaker)
Expansion Slot	Support 1*M.2 2280 M-Key Slot (SATA/NVME) Support 1*MINI PCIE Slot (WIFI/3G/4G Optional)
Network	i3 10110U, i5 10210U, i5 8260U Intel i211-AT 1000M LAN i5 8260U version 2, i7 10810U Intel i225-V 2.5G LAN
Storage	1*M.2 2280 Slot, 1*2.5" SATA, Support RAID 0/1
Power Supply	DC 12V Input
Other Function	Auto power on when there is electricity, Timing boot, Wake On LAN, PXE boot, Watchdog(0~255 level), TPM2.0 security encryption
Work Temp	0°C ~ +40°C (Commercial HDD), -20°C ~ +50°C (Industrial SSD), Surface air flow
Work Humidity	5% ~ 95% non-condensing
Certifications	CE, CCC, FCC Class A, RoHS
Dimension	186*126.5*66 MM
Net Weight	1.3KG

