

DH20

Ultra-light ARM Thin Client supporting Microsoft RemoteFX, Citrix HDX, VMware View



Feature


- Ultra-light and fanless design
- Designed with 1.2GHz Dual-core ARM SoC
- Support Microsoft RemoteFX, Citrix HDX, VMware View
- Optional WLAN module
- Support Kensington lock and VESA mount

Specification	Model no.	DH20	
Processor	CPU	Dual-core 1.2 GHz (ARM Cortex A9) SoC	
Memory	RAM	Onboard DDR3 1GB	
Display	Resolution	Up to 1920 x 1200	
Audio	Speaker	x 1 (Build-in 1W internal speaker)	
Storage		Onboard eMMC 4GB/8GB	
I/O Physical	USB (1.1/2.0)	Front	x 2
		Rear	x 2
	Video	DVI	x 1 (DVI-D)
		VGA	x 1
	Audio	Mic-in	x 1
Line-out		x 1	
Networking	LAN	x 1 (RJ-45, 10/100/1000 Base T)	
	WLAN	x 1 (Optional)	
Environment	Temperature	Operation	32° to 95° F (0° to 35° C)
		Storage	-4° to 140° F (-20° to 60° C)
	Relative Humidity	20% to 80% non-condensing	
Power	Power Supply	24W, DC 12V /2A external power adapter	
Mounting	Foot Stand	H or V	Vertical
	VESA Bracket	Metal mounting kit for VESA standard (optional)	
Security	Kensington Lock	Yes	
OS Support		Linux	
Physical Characteristics	Chassis Housing	Plastic and metal	
	Dimension / Weight	Terminal	29(W) x 155(H) x 133(D) mm / NW : 0.6 KG
		Packing: Single Box	83 (W) x 232 (H) x 205 (D) mm / GW: 1.1 KG
Packing: Carton	662 (W) x 265 (H) x 355 (D) mm / GW: 13.2 KG, 12 boxes in one carton		
Regulatory Compliance		CE / FCC	


Specifications subject to change without notice.

Mechanical Layout/ Drawing

Front Side View



Rear Side View



Front Side View

1. Power Button / Power LED
2. USB 2.0 port x 2
3. Audio line-out jack
4. Mic-in jack

Rear Side View

5. USB 2.0 port x 2
6. RJ-45 LAN port
7. DVI-D port
8. VGA port
9. DC jack
10. Kensington lock

